

Forankring - Ankre

Best.nr.	Betegnelse	Teknisk spec.					Vægt
		Bor Ø (mm)	Boredybde min. (mm)	Emnetykkelse maks. (mm)	Gevindlængde (mm)	Tilspændingsmoment max. (Nm)	
	Gennemstiksanker - Rustfri						
	Gennemstiksanker, A4 Syrefast stål m. SS-ring formonteret m. skive DIN125 & møtrik DIN934						
1028.06.065	M6 x 65mm	6	30	30	40	5	15 g
1028.06.075	M6 x 75mm	6	30	40	28	5	18 g
1028.08.050	M8 x 50mm	8	40	5	20	15	23 g
1028.08.095	M8 x 95mm	8	40	50	60	15	36 g
1028.08.115	M8 x 115mm	8	40	70	84	15	44 g
1028.10.060	M10 x 60mm	10	50	5	25	25	46 g
1028.10.075	M10 x 75mm	10	50	20	45	25	50 g
1028.10.090	M10 x 90mm	10	50	35	55	25	62 g
1028.10.120	M10 x 120mm	10	50	65	85	25	75 g
1028.12.110	M12 x 110mm	12	60	40	67	45	103 g
1028.12.140	M12 x 140mm	12	60	70	100	45	123 g
1028.12.180	M12 x 180mm	12	60	110	50	45	460 g
1028.16.145	M16 x 145mm	16	75	60	90	110	240 g
1028.20.160	M20 x 160mm	20	120	55	70	240	430 g
1028.20.220	M20 x 220mm	20	120	115	75	240	534 g
	<i>Gennemstiksanker kan anvendes til forankring af stål- og trækonstruktioner på beton eller sten.</i>						

