

# Blindnitemøtrik - Stål

Best.nr.	Betegnelse	Teknisk spec.							Moment max. (Nm.)
		d2 mm. udv.dia	d3 mm. hoveddia.	L mm. længde	S mm. hovedhøjde	Ø mm. borddia.	Træk (N.)		
	<b>Blindnitemøtrik med undersænket hoved og anti rotation (åben-model)</b>								
	<b>Materiale: Elforzinket stål</b>								
	<b>d1 mm. gevind / K mm. klemområde</b>								
1073.04.035	M4 -(2,0-3,5mm.)	5.9	9.0	11.5	1.5	ø6	7,300	4	
1073.05.040	M5 -(2,0-4,0mm.)	6.9	10.0	13.5	1.5	ø7	11,450	7	
1073.06.045	M6 -(2,0-4,5mm.)	8.9	12.0	16.0	1.5	ø9	16,900	15	
1073.08.030	M8 -(1,2-3,0mm.)	10.9	14.0	16.0	1.5	ø11	24,200	26	
1073.08.045	M8 -(2,0-4,5mm.)	10.9	14.0	19.0	1.5	ø11	24,200	26	
1073.10.045	M10 -(2,0-4,5mm.)	12.9	14.7	21.0	1.5	ø13	28,650	45	
1073.10.060	M10 -(3,5-6,0mm.)	12.9	14.7	21.0	1.5	ø13	28,650	45	

