

Best.nr.	Betegnelse	Teknisk spec.						Bærekraft (kg)	Illustration & symbol
		M (mm)	B (mm)	b (mm)	L (mm)	S (mm)			
	Gevindbøsning til firkantrør								
	Prop i sort kunstof-materiale og indsats i forniklet messing.								
	Udv. / Indv. / Tykkelse								
2015.30.008	30mm / 27mm / 1,5mm	M8	30	27.5	33	27	500		
2015.30.010	30mm / 27mm / 1,5mm	M10	30	27.5	33	27	500		
2015.30.012	30mm / 27mm / 1,5mm	M12	30	27.5	33	27	500		
2015.30.014	30mm / 27mm / 1,5mm	M14	30	27.5	33	27	500		
2015.30.016	30mm / 27mm / 1,5mm	M16	30	27.5	33	27	500		
2016.30.008	30mm / 26mm / 2,0mm	M8	30	26.5	33	27	500		
2016.30.010	30mm / 26mm / 2,0mm	M10	30	26.5	33	27	500		
2016.30.012	30mm / 26mm / 2,0mm	M12	30	26.5	33	27	500		
2016.30.014	30mm / 26mm / 2,0mm	M14	30	26.5	33	27	500		
2016.30.016	30mm / 26mm / 2,0mm	M16	30	26.5	33	27	500		
2015.40.008	40mm / 37mm / 1,5mm	M8	40	37.5	43	35	800		
2015.40.010	40mm / 37mm / 1,5mm	M10	40	37.5	43	35	800		
2015.40.012	40mm / 37mm / 1,5mm	M12	40	37.5	43	35	800		
2015.40.014	40mm / 37mm / 1,5mm	M14	40	37.5	43	35	800		
2015.40.016	40mm / 37mm / 1,5mm	M16	40	37.5	43	35	800		
2015.40.020	40mm / 37mm / 1,5mm	M20	40	37.5	43	35	800		
2016.40.008	40mm / 36mm / 2,0mm	M8	40	36.5	43	35	1.000		
2016.40.010	40mm / 36mm / 2,0mm	M10	40	36.5	43	35	1.000		
2016.40.012	40mm / 36mm / 2,0mm	M12	40	36.5	43	35	1.000		
2016.40.014	40mm / 36mm / 2,0mm	M14	40	36.5	43	35	1.000		
2016.40.016	40mm / 36mm / 2,0mm	M16	40	36.5	43	35	1.000		
2016.40.020	40mm / 36mm / 2,0mm	M20	40	36.5	43	35	1.000		
2017.40.008	40mm / 35,5mm / 2,5mm	M8	40	35.5	43	35	1.000		
2017.40.010	40mm / 35,5mm / 2,5mm	M10	40	35.5	43	35	1.000		
2017.40.012	40mm / 35,5mm / 2,5mm	M12	40	35.5	43	35	1.000		
2017.40.014	40mm / 35,5mm / 2,5mm	M14	40	35.5	43	35	1.000		
2017.40.016	40mm / 35,5mm / 2,5mm	M16	40	35.5	43	35	1.000		
2017.40.020	40mm / 35,5mm / 2,5mm	M20	40	35.5	43	35	1.000		
2018.40.008	40mm / 34,5mm / 3,0mm	M8	40	34.5	43	35	1.000		
2018.40.010	40mm / 34,5mm / 3,0mm	M10	40	34.5	43	35	1.000		
2018.40.012	40mm / 34,5mm / 3,0mm	M12	40	34.5	43	35	1.000		
2018.40.014	40mm / 34,5mm / 3,0mm	M14	40	34.5	43	35	1.000		
2018.40.016	40mm / 34,5mm / 3,0mm	M16	40	34.5	43	35	1.000		
2018.40.020	40mm / 34,5mm / 3,0mm	M20	40	34.5	43	35	1.000		
2019.40.008	40mm / 32mm / 4,0mm	M8	40	32.5	43	35	1.000		
2019.40.010	40mm / 32mm / 4,0mm	M10	40	32.5	43	35	1.000		
2019.40.012	40mm / 32mm / 4,0mm	M12	40	32.5	43	35	1.000		
2019.40.014	40mm / 32mm / 4,0mm	M14	40	32.5	43	35	1.000		
2019.40.016	40mm / 32mm / 4,0mm	M16	40	32.5	43	35	1.000		
2019.40.020	40mm / 32mm / 4,0mm	M20	40	32.5	43	35	1.000		
	<ul style="list-style-type: none"> • Proppen i glasfiberforstærket polyamidbaseret (PA) technopolymer • Gevindindsats i forniklet messing 								
	<p>Gevindbøsningen anvendes til enkelt montage af maskinsko til firkantprofiler - Indsatsen presses let i profilet.</p> <p>Maskinskoen monteres i enden af gevindbøsningen.</p>								

